UN38.3 Test Summary

The following product has been evaluated according to the 6th revised edition of the UN Manual of Tests and Criteria.

We, LG Chem, Ltd., hereby certify that this battery meets the requirements of the regulation for transportation of lithium-ion cells, batteries and single cell batteries.

| Manufacturer's contact information | LG Chem, Ltd. Address: 128 Yeoui-Daero, Yeongdeungpo-gu, SEOUL, 150-721, REPUBLIC OF KOREA Telephone: +82-10-7742-5427 E-mail: kkammy@lgchem.com Website: www.lgchem.com | | | |
|------------------------------------|---|------------------------|--------------------------------|------|
| Test Laboratory information | LG Chem, Ltd. / RESEARCH PARK Address: 188 Munjiro, Yuseong-gu, Daejeon, 305-738, REPUBLIC OF KOREA Telephone: +82-10-4808-7362 E-mail: Milkis@lgchem.com Website: www.lgchem.com | | | |
| Description | | List of Test Completed | | |
| Test Report Number | QDI-200908-B-SH128064P8S1 | UN 38.3 Tests | Test 1. Altitude Simulation | Pass |
| Date of test report | 2020. 09. 08 | | Test 2. Thermal Test | Pass |
| Item / Cell Type | Lithium ion Battery / Pouch | | Test 3. Vibration | Pass |
| Model name | SH128064P8S1 | | Test 4. Shock | Pass |
| Nominal voltage | 128.45 V | | Test 5. External Short Circuit | Pass |
| Capacity / Energy | 64.1 Ah / 8.225 kWh | | Test 6. Impact or Crush | Pass |
| Weight | Max 66.0 kg | | Test 7. Overcharge | N/A |
| Dimensions | 147.0(L)*490.0(W)*798.4(H) mm | | Test 8. Forced Discharge | Pass |

Reviewed By: MinJe Woo Professional Global Standard Certification Team LG Chem, Ltd. E-mail: Milkis@lgchem.com

A

Approved By: DaeHo Nam Team Leader Global Standard Certification Team LG Chem, Ltd. E-mail: kkammy@lgchem.com

